



**L3HARRIS™**  
FAST. FORWARD.

# RF-6705-SW001

## Tactical Chat™ IP

FEATURES	
<b>Configuration and Deployment</b>	L3Harris Communications Planning Application (CPA) and Radio Programming Application (RPA) import Centralized address book maintenance Easily exchange configuration data with other stations Automatic discovery of LAN users Direct connection to Falcon II® and Falcon III® radios
<b>Message Generation</b>	Select station from address book or specify IP address Define, select, and transmit predefined text messages Message composition via keyboard entry (soft keyboard for PDA), or handwriting recognition (if resident on PDA device) Attach and transmit files, including images Save and view chat log
<b>Message Transmission</b>	Automatic message compression Point-to-point (ARQ) and subnet-directed broadcast (non-ARQ) message transmission Resume failed file transfer from point of failure Automatic message logging Abort message transfer
<b>Supported L3Harris Equipment</b>	RF-5800H-MP, AN/PRC-150 (C), RF-5800V-MP, RF-5800V-HH, RF-5800M-HH, AN/PRC-117F (C), RF-7800V-HH, AN/PRC-117G, AN/PRC-152, AN/PRC-152A, RF-7800H, RF-7800M-MP, RF-7800M-HH, RF-7800S-TR, RF-7800S-V

MINIMUM PC REQUIREMENTS	
<b>CPU</b>	Intel Pentium 500 MHz or minimum required for OS, whichever is greater
<b>Operating System</b>	Windows 2008 Server, Windows 2003 Server, Windows 2000, Windows XP, Windows XP Tablet Edition, Windows Vista, Windows 7 (English language version only)
<b>Memory (RAM)</b>	512MB or minimum required for OS, whichever is greater
<b>Display</b>	800 x 600 resolution
<b>I/O</b>	Standard RS-232C serial port Ethernet USB

MINIMUM PDA REQUIREMENTS	
<b>CPU</b>	Intel StrongArm, Intel XScale
<b>Platform</b>	Windows Mobile 6.1, 6.0 and 5.0
<b>Memory (RAM)</b>	128 MB
<b>Display</b>	240 x 320 color TFT
<b>I/O</b>	Standard RS-232C serial port Ethernet USB



The RF-6705-SW001 is an easy-to-use data application for text message and file sharing among fielded and networked data terminals. Tactical Chat IP supports both point-to-point and subnet-directed broadcast data transfer among members of an IP subnetwork. Users can leverage the IP data capabilities of Falcon II® and Falcon III® radios to exchange messages between wired (e.g. Ethernet® LAN) and wireless network users. The RF-6705-SW001 allows quick messaging or file transfer to a predefined network station. Users can also chat with one or multiple users via broadcast or subnet broadcast chat. The RF-6705-SW001 runs on both Windows®, Windows mobile PDAs and is interoperable with the RF-6705AN-SW001 Android™ version.

#### ORDERING INFO

RF-6705-SW001	CD Media
---------------	----------

#### ACCESSORIES

RF-3577	Personal Computer Series
---------	--------------------------

RF-3587	Series of Rugged PDAs
---------	-----------------------

RF-6705-SW001 Tactical Chat™ IP

© 2020 L3Harris Technologies, Inc. | 04/2020 SP162

#### Non-Export Controlled Information

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.



**L3HARRIS™**  
FAST. FORWARD.

1025 W. NASA Boulevard  
Melbourne, FL 32919