



## N27 MARKER BEACON ANTENNAS

The N27 Antennas are rugged, lightweight antennas for the reception of 75 megahertz marker beacon signals. These low-drag antennas are designed for simple external mounting and require no cutting of airframe structural members. The largest hole required in the skin is for the connector.

Moisture proofing is assured by the dielectric foam-filled, white polyester-fiberglass radomes. These Skydrol-resistant housings are fitted with metal leading edges for erosion protection. The N27 Antennas are designed to meet the performance specifications of antennas AT-134 and AT-536.

PARAMETER	SPECIFICATION
<b>Electrical</b>	
Frequency range	74.75 – 75.25 MHz
Center frequency	75.0 MHz
VSWR	
At midband	< 1.5:1
74.8 – 75.2 MHz	< 5.0:1
Gain (relative to isotropic)	-9 dB
Impedance	50 Ohms
Polarization	Horizontal
Power handling	Receive only
<b>Mechanical</b>	
Connector	
N27-1	TNC female
N27-2	C female
N27-3	BNC female
Weight	10 oz
Type of construction	Dielectric foam filled fiberglass housing with metal leading edge.
Military	Qualified to MIL-T-5422E
FAA	TSO C35c
D0108 ENV CAT.	ABAAAAAX



### KEY FEATURES

- > Rugged, Skydrol-resistant radome
- > Metal leading edge
- > Simplified mounting

For further details and specifications, contact the factory at [antenna.info@L3Harris.com](mailto:antenna.info@L3Harris.com)

#### N27 Marker Beacon Antennas

© 2020 L3Harris Technologies, Inc. | 08/2020 | 60312 | TRP

Cleared by OFOISR for Public Release | 1099-141 (M1)

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.

