

MIDS-LVT(2)/(11) RUGGEDIZED MOBILE SYSTEM

MIDS Support Equipment

The L3Harris MIDS-LVT(2)/(11) Ruggedized Mobile System is a small, transportable case unit for the MIDS-LVT(2)/(11) terminal. Outfitted with all of the support equipment required to fully operate a MIDS-LVT(2)/(11) terminal, this mobile system alleviates all of the hardware challenges normally associated with getting your terminal integrated with your Link 16 host and operational in the network.

PRODUCT DESCRIPTION

The mobile system features the L3Harris Multi-Platform Integrated Controller (MIC), a rugged control unit that offers both local and remote operation through an easy-to-operate web interface:

- > Terminal Power
- > Power Conditioner Failure Indication
- > Air Filter Service Indication
- > Blower Failure Indication
- > Platform (IOIDENT) Configuration
- > Crypto Zeroize

The MIC offers a standard fill connector interface to the MIDS-LVT for ease of loading crypto with standard fill devices.

The mobile system also includes the L3Harris Multi-Platform Audio Component (MAC), a rugged interface unit that provides independent or simultaneous dual-channel Link 16 voice (receive and transmit). It features a custom built 30 W quad-speaker system that has been tuned to enhance audio quality. The MAC is compatible with most headsets and handsets and is also controlled through the same, intuitive web interface that is provided by the MIC.

This full-complement system contains all the hardware needed to power and control your terminal. It is suitable for use in all venues, including operational, training, demonstrations and testing.







Rugged, Transportable, Ready-to-Use

KEY FEATURES

- Multi-Platform Integrated Controller (MIC)
- > Multi-Platform Audio Component (MAC)
- MIDS-LVT(2)/(11) sliding shelf for easy access
- > Power and I/O panel for input power to the mobile system as well as standard interfaces to the MIDS-LVT(2)/(11) terminal:
 - MIDS Support Port/Ethernet (RJ45)
 - Link 16 1PPS ETR Input 10v, 50ohm (BNC)
 - Link 16 Antenna A (NTYPE)
 - MIC Web Interface (RJ45)
 - GPS 1PPS Output (BNC)
 - GPS USB Serial Console (USB-B)
- > Enhanced DC power supply. It is preprogrammed to provide ± 140 VDC power required by the MIDS-LVT(2)/(11) terminal
- Integrated IFF 1030/1090 MHz notch filter for added protection and mitigation of IFF interference
- Internal rack GPS to provide Link 16 1PPS ETR strobe and access to NMEA streams for an external host system via a USB serial connection
- > Link 16 RF termination load is installed in the system to provide Antenna B with proper termination for safe operation

SPECIFICATIONS

PERFORMANCE

> Input Power: 120 VAC 60 Hz, 20 amp (IEC C20) 230/240

VAC 50 Hz, 10 amp (IEC C14)

> Dimensions: 18.1" x 22.5" x 34.5"> Weight: 200 lbs (Approximate)

STANDARD CABLES

> W2, W3 and W7: Link 16 Voice/Data/Control

> W4: Crypto

> W10 and W11: Link 16 RF Cables

> PSA 28VDC: Power Cable

STANDARD ACCESSORIES

- > Input Power Cables:
 - 120 VAC NEMA 5-20P to IEC C19
 - 230/240 VAC AS/NZ4417 to IEC C13
 - 230/240 VAC CEE 7/7 EURO SCHUKO to IEC C13
 - (please specify if other international cables are required)
- > BNC to BNC 1PPS Jumper Cable
- > H-250 Handset
- > 4x Ethernet Cables
- > USB-A to USB-B Cable
- > User Guide

PART DESCRIPTION

> MIDS-LVT(2)/(11) Ruggedized Mobile Rack

MIDS-LVT(2)/(11) Ruggedized Mobile System

© 2023 L3Harris Technologies, Inc. | 01/2023 | BCS | 23-DSD-291 | Rev-201

These item(s)/data have been reviewed in accordance with the International Traffic in Arms Regulations (ITAR), 22 CFR part 120.11, and the Export Administration Regulations (EAR), 15 CFR 734(3)(b)(3), and may be released without export restrictions.

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.

Use of U.S. DoD visual information does not imply or constitute DoD endorsement.



1025 W. NASA Boulevard Melbourne, FL 32919 t 833 537 6837 CSW.Products@L3Harris.com