



L3HARRIS®
FAST. FORWARD.


ADVANCED ELECTRIC PROPULSION SYSTEM (AEPS)

High-powered solar electric propulsion

SYSTEM PERFORMANCE	
Input Voltage Range	95V – 140V
Number of Cycles	5000
Total Impulse	10 [^] 8 N-sec
Efficiency	> 60% (at 13.3 kW system input power)
Mass	< 99 kg (including XFC and harnessing)
Life Capability	> 15 yrs

HALL THRUSTER	
Propellant	Xenon
Mass	< 47 kg
Envelope	530 mm (diam) x 210 mm (height)
Low Power Performance	390 mN, 1900 seconds (at 300V, 20.8A)
High Power Performance	600 mN, 2800 seconds (at 600V, 20.8A)
Efficiency	> 65% (600V, 20.8A)

POWER PROCESSING UNIT	
Mass	< 50 kg
Envelope	520 mm x 900 mm x 200 mm
Efficiency	> 94% (at 13.3 kW input power)
Command Interface	Mil-Std-1553B
Discharge Output Power	3.0 kW to 12.5 kW
Features	Flexible and automated startup, monitoring and fault protection of thruster and XFC



L3Harris' advanced electric propulsion system will significantly advance the nation's commercial space capabilities and enable deep space exploration missions.

Advanced Electric Propulsion System (AEPS)

© 2024 L3Harris Technologies, Inc. | 07/2024 | L26279

NON-EXPORT CONTROLLED: THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. Visit [L3Harris.com](https://www.l3harris.com) for more information.

L3Harris Technologies, Inc.

1025 W. NASA Boulevard
Melbourne, FL 32919

[L3Harris.com](https://www.l3harris.com)